

## TERMOSTATICI - THERMOSTATIC MIXERS

ONE

### FINITURE - FINISHES



029.0A0.01.0T9.009.00R.3 1/2" + Kit P.393 + Kit P.304 + Kit P.404(x6)  
 030.0A0.01.0T9.009.00R.3 3/4" + Kit P.393 + Kit P.304 + Kit P.404(x6)

Art. 029.0A0.01.0T9.009.00R.3 1/2"  
 030.0A0.01.0T9.009.00R.3 3/4"

Miscelatore termostatico incasso con deviatore 3 vie + uscita combinata. **Senza gruppo soffione, gruppo doccetta e getti per il corpo**

Thermostatic built-in mixer with 3 way diverter and shared outlet. **Without head shower set, hand shower set and body spray**

KIT P.393	KIT P.304	KIT P.404 (x1)
Gruppo soffione	Gruppo doccetta	Getto per il corpo
Head shower set	Hand shower set	Body spray

### OPERATING SPECIFICATIONS

Hot water supply temperature:  
 Maximum: 85°C - Advisable: 65°C  
 Minimum: 5°C  
 Operating Pressure  
 Maximum: 5 Bar  
 Minimum: 0.1 Bar



### Disegno Tecnico - Technical Drawing

